



EUM280
Excel Universals Mills with Autocycles
1-260-150



Product details

- Extra Heavy Duty construction of the machine enables you to take large cuts.
- Auto Cycles reduce the production time and increase your profitability. Power Feed & Rapid in all directions, i.e. X,Y, & Z for speed and ease of use.
- Controls are positioned for easy accessibility and operator use.
- Centralised Forced Lubrication ensures lubrication to all parts otherwise inaccessible.

Specifications

| | |
|---------------------------------|-----------------|
| Approx Weight | 2000Kgs |
| Cross Travel Hand | 250mm |
| Cross Travel Power | 230mm |
| Feed Rate | 12.5--630mm/min |
| Height | 1630mm |
| Length | 1710mm |
| Longitudinal Travel Hand | 865mm |
| Longitudinal Travel Power | 845mm |
| Model | FU281 |
| No of T Slots in Table | 3 |
| Number of Spindle Speeds | 18 |
| Overall Length of Table | 1650mm |
| Rapid Feed Rate | 2500mm/min |
| Spacing of T Slots | 63mm |
| Speed Range | 40-2000RPM |
| Spindle Motor | 5.5KW (7.5HP) |
| Spindle Nose ISO | ISO 50 |
| Table Swivel Left Right | 45 |
| Throat Depth With Vertical Head | 349mm |
| Vertical Travel | 410mm |