



Excel Hydraulic Swing Beam Shear EHS Range



Product details

- Excels range of hydraulic swing beam shears range from 4mm x 2000mm capacity up to 20mm x 4000mm capacity.
- Machines are of high rigidity and strength
- The sheet is moved easily by the rolling balls and support block located on the table to ensure the surface quality of the sheet to be cut.
- Hydraulic drive, swing beam, the return of the knife beam is smooth and prompt by the accumulator or nitrogen cylinder.
- The stroke of knife beam can be adjusted steplessly
- The position of low blade can be adjusted to ensure the equilibrium of the gap between blades after regrinding.
- Adjustment of the gap between blades is portable and prompt. The value of the gap is indicated on a dial
- The back gauge is motorised adjustable and manual fine adjustment.
- The adjusted value is shown on the numerator on the front of the machine is digital display
- The cutting times are shown with the counter on the front of the machine
- Pre-selection of single or continuous stroke
- Equipped with lighting alignment (Shadow light) device

Specifications

Contact Excel Machine Tools

By e-mail sales@excelmachinetools.co.uk

Excel Machine Tools
Colliery Lane, Exhall,
Coventry, CV7 9NW, UK

National Tel: (024) 7636 5255
National Fax: (024) 7636 6666
International Tel: +44 (24) 7636 5255
International Fax: +44 (24) 7636 6666

www.excelmachinetools.co.uk